

according to Commission Regulation (EU) 2020/878 as amended

**TELKYD T300 E**

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

- 1.1. Product identifier**  
Substance / mixture TELKYD T300 E  
UFI mixture WM9W-J00A-D00K-JG0E  
Other mixture names  
Email vrchní průmyslový syntetický lesklý
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**  
**Mixture's intended use**  
Urethaned enamel glossy. For professional use only.  
**Main intended use**  
PC-PNT-3 Paints/coatings - Protective and functional  
**Mixture uses advised against**  
The product should not be used in ways other than those referred in Section 1.  
Exposure scenario is attached to the Safety Data Sheet.
- 1.3. Details of the supplier of the safety data sheet**  
**Manufacturer**  
Name or trade name BARVY A LAKY TELURIA,s.r.o.  
Address č.p.1, Skrchov, 679 61  
Czech Republic  
Identification number (CRN) 43420371  
VAT Reg No CZ43420371  
Phone +420 516 474 211  
E-mail info@teluria.cz  
Web address http://www.bal.cz
- Competent person responsible for the safety data sheet**  
Name BARVY A LAKY TELURIA,s.r.o.  
E-mail info@teluria.cz
- 1.4. Emergency telephone number**  
European emergency number: 112

**SECTION 2: Hazards identification**

- 2.1. Classification of the substance or mixture**  
**Classification of the mixture in accordance with Regulation (EC) No 1272/2008**  
The mixture is classified as dangerous.

Flam. Liq. 3, H226  
Skin Irrit. 2, H315  
Skin Sens. 1A, H317  
Eye Irrit. 2, H319  
STOT SE 3, H335  
Carc. 1B, H350  
Repr. 1B, H360D  
STOT RE 2, H373  
Aquatic Chronic 3, H412

Full text of all classifications and hazard statements is given in the section 16.

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### Most serious adverse physico-chemical effects

Flammable liquid and vapour.

### Most serious adverse effects on human health and the environment

May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation. Causes serious eye irritation. Causes skin irritation. May cause cancer. May damage the unborn child. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

### Hazard pictogram



### Signal word

Danger

### Hazardous substances

xylene ( mixture of isomers and ethylbenzene )

2-butanone oxime

2-ethylhexanoic acid, zirconium salt

Cobalt bis(2-ethylhexanoate)

### Hazard statements

|       |  |
|-------|--|
| H226  | Flammable liquid and vapour.                                       |
| H315  | Causes skin irritation.  |
| H317  | May cause an allergic skin reaction.                               |
| H319  | Causes serious eye irritation.                                     |
| H335  | May cause respiratory irritation.                                  |
| H350  | May cause cancer.  |
| H360D | May damage the unborn child.                                       |
| H373  | May cause damage to organs through prolonged or repeated exposure. |
| H412  | Harmful to aquatic life with long lasting effects.                 |

### Precautionary statements

|           |  |
|-----------|--|
| P201      | Obtain special instructions before use.  |
| P210      | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P261      | Avoid breathing vapours/spray.   |
| P264      | Wash hands and exposed parts of the body thoroughly after handling.                            |
| P280      | Wear protective gloves/protective clothing/eye protection.                                     |
| P308+P313 | IF exposed or concerned: Get medical advice/attention.   |
| P312      | Call a doctor if you feel unwell.  |

### Supplemental information

Restricted to professional users.

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

|            |   |
|------------|---|
| Density    | 1.25-1.4 g/cm <sup>3</sup> at 23 °C (EN ISO 2811-1) |
| VOC        | 0,31-0,35 kg/kg                                     |
| TOC        | 0,26-0,31 kg/kg                                     |
| Dry matter | ≥50 % volume  |

### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Substances are neither listed in Annex XIV of REACH nor on the REACH candidate list of substances of very high concern (SVHC).

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### Chemical characterization

Mixture of pigments and fillers in solution of alkyd and alkyd-urethane resins in organic solvents with addition of additives and driers.

The mixture contains a reaction mixture of o, m, p-xylene and ethylbenzene (ethylbenzene content <26%).

**Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment**

| Identification numbers  | Substance name                                 | Content in % weight | Classification according to Regulation (EC) No 1272/2008  | Note |
|---|--|---------------------|---|------|
| EC: 905-562-9<br>Registration number:<br>01-2119555267-33   | xylene ( mixture of isomers and ethylbenzene ) | 22-25               | Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>Acute Tox. 4, H312+H332<br>Skin Irrit. 2, H315<br>Eye Irrit. 2, H319<br>STOT SE 3, H335<br>STOT RE 2, H373   | 1, 3 |
| Index: 649-356-00-4<br>EC: 918-668-5<br>Registration number:<br>01-2119455851-35                  | hydrocarbons, C9, aromatics                    | 5,7-6,7             | Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>STOT SE 3, H335, H336<br>Aquatic Chronic 2, H411<br>EUH066   | 2, 5 |
| Index: 607-195-00-7<br>CAS: 108-65-6<br>EC: 203-603-9<br>Registration number:<br>01-2119475791-29 | 2-methoxy-1-methylethyl acetate                | 3,6-4,6             | Flam. Liq. 3, H226  | 3    |
| Index: 616-014-00-0<br>CAS: 96-29-7<br>EC: 202-496-6<br>Registration number:<br>01-2119539477-28  | 2-butanone oxime                               | 0,9-0,99            | Acute Tox. 3, H301<br>Acute Tox. 4, H312<br>Skin Irrit. 2, H315<br>Skin Sens. 1, H317<br>Eye Dam. 1, H318<br>STOT SE 3, H336<br>Carc. 1B, H350<br>STOT SE 1, H370 (upper respiratory tract)<br>STOT RE 2, H373 (blood system)<br>Specific concentration limit:<br>ATE Dermal = 1100 mg/kg bw<br>ATE Oral = 100 mg/kg bw |      |

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

| Identification numbers   | Substance name   | Content in % weight | Classification according to Regulation (EC) No 1272/2008  | Note |
|--|--|---------------------|---|------|
| Index: 649-327-00-6<br>EC: 918-481-9<br>Registration number:<br>01-2119457273-39 | Hydrocarbons, C10 – C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics | 0,8-1               | Asp. Tox. 1, H304<br>EUH066   | 2, 5 |
| EC: 927-241-2<br>Registration number:<br>01-2119471843-32                        | hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics      | 0,65-1              | Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>STOT SE 3, H336<br>Aquatic Chronic 3, H412                             |      |
| CAS: 22464-99-9<br>EC: 245-018-1<br>Registration number:<br>01-2119979088-21     | 2-ethylhexanoic acid, zirconium salt                                     | 0,34-0,4            | Repr. 1B, H360D   | 4    |
| CAS: 136-51-6<br>EC: 205-249-0<br>Registration number:<br>01-2119978297-19       | calcium bis(2-ethylhexanoate)  | 0,22-0,26           | Eye Dam. 1, H318<br>Repr. 1B, H360D   | 4    |
| CAS: 136-52-7<br>EC: 205-250-6<br>Registration number:<br>01-2119524678-29       | Cobalt bis(2-ethylhexanoate)   | 0,12-0,14           | Skin Sens. 1A, H317<br>Eye Irrit. 2, H319<br>Repr. 1A, H360FD<br>Aquatic Acute 1, H400<br>Aquatic Chronic 3, H412 | 4    |

### Notes

- 1 Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- 2 Note P: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.
- 3 A substance for which exposure limits are set.
- 4 The use of the substance is restricted by Annex XVII of REACH Regulation
- 5 Fulfilled Note P

Full text of all classifications and hazard statements is given in the section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

#### If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

### If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

### If swallowed

Rinse out the mouth with clean water. DO NOT INDUCE VOMITING! Provide medical treatment. For persons with no symptoms, call the Toxicological Information Centre to decide about the need of medical treatment; provide information about the substances or composition of the product from the original packaging or the Safety Data Sheet of the product.

## 4.2. Most important symptoms and effects, both acute and delayed

### If inhaled

May cause respiratory irritation.

### If on skin

May cause an allergic skin reaction.

### If in eyes

Causes serious eye irritation.

### If swallowed

Irritation, nausea.

## 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment. If you see a doctor, take this safety data sheet with you.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

#### Unsuitable extinguishing media

Water - full jet.

### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

### 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

For workers apart from emergency teams: Avoid inhalation of vapour, prevent skin and eye contact. Wear appropriate protective clothing and gloves. Wear eye protection and face shield if necessary. Use suitable respiratory protection. In closed spaces, ensure fresh air supply. Eliminate all ignition sources. No smoking and no open fire. Keep unnecessary personnel away.

For members of emergency teams: Use appropriate personal protective equipment – protective clothing with antistatic finish and impermeable work shoes. Treat unprotected skin with barrier cream. Anti-chemical protective gloves. For short-time exposure or low concentration, use respirator with organic vapour and dust filter (protection level A/P2); for high concentration and long-term exposure, self-contained respirator is necessary.

#### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water. If possible prevent leakage, close container and place damaged container in protective container.

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

#### 6.4. Reference to other sections

See the Section 7, 8 and 13.

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### 7.1.1. General health measures

Use the product after due familiarization with its hazard characteristics and proper training or training in its safe use. Do not eat, drink, smoke on the site. Wash your hands and other contaminated parts of body by soap and water before eating and after the use of product is finished. Abide by requirements on personal hygiene when working with hazardous chemical products.

Use technical equipment on the site to control human and environment exposure. Regularly inspect the equipment, ensure cleaning, timely maintenance and permanent functionality. When working, use the recommended personal protective equipment listed in 8.2 of the Safety Data Sheet and in Annex to the Safety Data Sheet. Keep the protective clothing and protective equipment sound and clean. Immediately replace the damaged protective aids for sound ones. Keep the site, tools and aids clean and in sound state. On the site, keep the product in labelled containers or tanks. Store product waste and wastes contaminated by the product in suitable and properly labelled vessels located on designated marked and protected places. Ensure long-term storing of wastes containing the product outside the site.

##### 7.1.2. Fire precautions

When using the product, prevent potential ignition or explosion of the mixture of product vapour and air caused by contact with open flame, sparks, extremely hot surfaces, electrostatic discharges. Do not smoke on the site, use non-sparking tools. Places with increased occurrence of the vapour-air mixture need to be ventilated to prevent formation of explosive mixtures. Solvent vapours are heavier than air. The site should be protected from electrostatic discharges.

##### 7.1.3. Environmental precautions

Handle the product on a site technically adapted to avoid accidental leakage to sewerage systems, water or soil. Product waste and wastes contaminated by the product to be disposed of as hazardous waste. Waste water contaminated by the product may only be discharged to water reservoirs after the product components are properly removed in a waste water treatment plant or in other appropriate treatment plant able to remove drifted product components from water. Do not pour the product to waste water. Emissions of solvent from point sources are subjected to control requirements acc. to air protection regulations.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store the product in properly marked, closed containers in well ventilated spaces at 5 – 25 °C. The storages must meet the requirements on storing of flammable liquids and substances hazardous for aquatic life and soil. Protect from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. Store away from oxidising substances and strong acids. Do not store with food, drinks, feed material, medicines. Storages should be protected from static electricity. First aid kit and water suitable for eye rinsing should be available. Keep away from products that are corrosive to metals (eg acids or pool chemicals).

|                     |  |
|---------------------|--|
| Storage class       | 3A - Flammable liquids (flash point below 55 °C) |
| Storage temperature | min 5 °C, max 25 °C                              |

#### The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

#### 7.3. Specific end use(s)

Use in coating compositions was assessed for the individual substances of the mixture. Conditions of safe use of the registered coating composition components specified in exposure scenarios to SDSs of the components are incorporated to this Safety Data Sheet and its Annex.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

##### European Union

##### Commission Directive 2000/39/EC

| Substance name (component) | Type        | Value                 | Note |
|----------------------------|-------------|-----------------------|------|
| xylenes                    | OEL 8 hours | 221 mg/m <sup>3</sup> | Skin |

according to Commission Regulation (EU) 2020/878 as amended

**TELKYD T300 E**

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

**European Union**
**Commission Directive 2000/39/EC**

| Substance name (component)                      | Type           | Value                 | Note |
|---|----------------|-----------------------|------|
| xylenes   | OEL 8 hours    | 50 ppm                | Skin |
|   | OEL 15 minutes | 442 mg/m <sup>3</sup> |      |
|   | OEL 15 minutes | 100 ppm               |      |
| 2-methoxy-1-methylethyl acetate (CAS: 108-65-6) | OEL 8 hours    | 275 mg/m <sup>3</sup> | Skin |
|   | OEL 8 hours    | 50 ppm                |      |
|   | OEL 15 minutes | 550 mg/m <sup>3</sup> |      |
|   | OEL 15 minutes | 100 ppm               |      |

**DNEL**

| 2-butanone oxime    |                   |                           |                          |                     |        |
|---------------------|-------------------|---------------------------|--------------------------|---------------------|--------|
| Workers / consumers | Route of exposure | Value                     | Effect                   | Value determination | Source |
| Workers             | Inhalation        | 0.028 mg/m <sup>3</sup>   | Chronic effects systemic |                     |        |
| Workers             | Inhalation        | 0.9 mg/m <sup>3</sup>     | Chronic effects local    |                     |        |
| Workers             | Dermal            | 0.004 mg/kg bw/day        | Chronic effects systemic |                     |        |
| Consumers           | Inhalation        | 0.00482 mg/m <sup>3</sup> | Chronic effects systemic |                     |        |
| Consumers           | Inhalation        | 0.43 mg/m <sup>3</sup>    | Chronic effects local    |                     |        |
| Consumers           | Oral              | 0.0016 mg/kg bw/day       | Chronic effects systemic |                     |        |

| 2-ethylhexanoic acid, zirconium salt |                   |                         |                          |                     |        |
|--------------------------------------|-------------------|-------------------------|--------------------------|---------------------|--------|
| Workers / consumers                  | Route of exposure | Value                   | Effect                   | Value determination | Source |
| Workers                              | Inhalation        | 32.97 mg/m <sup>3</sup> | Chronic effects systemic |                     |        |
| Workers                              | Dermal            | 6.49 mg/kg bw/day       | Chronic effects systemic |                     |        |
| Consumers                            | Inhalation        | 8.13 mg/m <sup>3</sup>  | Chronic effects systemic |                     |        |
| Consumers                            | Dermal            | 3.25 mg/kg bw/day       | Chronic effects systemic |                     |        |
| Consumers                            | Oral              | 2.5 mg/kg bw/day        | Chronic effects systemic |                     |        |

according to Commission Regulation (EU) 2020/878 as amended

**TELKYD T300 E**

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

**2-methoxy-1-methylethyl acetate**

| Workers / consumers | Route of exposure | Value                 | Effect                   | Value determination | Source |
|---------------------|-------------------|-----------------------|--------------------------|---------------------|--------|
| Workers             | Inhalation        | 275 mg/m <sup>3</sup> | Chronic effects systemic |                     |        |
| Workers             | Inhalation        | 550 mg/m <sup>3</sup> | Acute effects local      |                     |        |
| Workers             | Dermal            | 796 mg/kg bw/day      | Chronic effects systemic |                     |        |
| Consumers           | Inhalation        | 33 mg/m <sup>3</sup>  | Chronic effects systemic |                     |        |
| Consumers           | Inhalation        | 33 mg/m <sup>3</sup>  | Acute effects systemic   |                     |        |
| Consumers           | Dermal            | 320 mg/kg bw/day      | Chronic effects systemic |                     |        |
| Consumers           | Oral              | 36 mg/kg bw/day       | Chronic effects systemic |                     |        |

**calcium bis(2-ethylhexanoate)**

| Workers / consumers | Route of exposure | Value                   | Effect                   | Value determination | Source |
|---------------------|-------------------|-------------------------|--------------------------|---------------------|--------|
| Workers             | Inhalation        | 39.98 mg/m <sup>3</sup> | Chronic effects systemic |                     |        |
| Workers             | Dermal            | 5.7 mg/kg bw/day        | Chronic effects systemic |                     |        |
| Consumers           | Inhalation        | 9.68 mg/m <sup>3</sup>  | Chronic effects systemic |                     |        |
| Consumers           | Dermal            | 2.83 mg/kg bw/day       | Chronic effects systemic |                     |        |
| Consumers           | Oral              | 2.83 mg/kg bw/day       | Chronic effects systemic |                     |        |

**Cobalt bis(2-ethylhexanoate)**

| Workers / consumers | Route of exposure | Value                    | Effect                   | Value determination | Source |
|---------------------|-------------------|--------------------------|--------------------------|---------------------|--------|
| Workers             | Inhalation        | 0.2351 mg/m <sup>3</sup> | Chronic effects local    |                     |        |
| Consumers           | Inhalation        | 0.037 mg/m <sup>3</sup>  | Chronic effects local    |                     |        |
| Consumers           | Oral              | 0.0276 mg/kg bw/day      | Chronic effects systemic |                     |        |
| Consumers           | Inhalation        | 0.175 mg/m <sup>3</sup>  | Chronic effects systemic |                     |        |

according to Commission Regulation (EU) 2020/878 as amended

**TELKYD T300 E**

 Creation date 03rd August 2016  
 Revision date 25th September 2023 Version 5.0

**hydrocarbons, C9, aromatics**

| Workers / consumers | Route of exposure | Value                 | Effect                   | Value determination | Source |
|---------------------|-------------------|-----------------------|--------------------------|---------------------|--------|
| Consumers           | Inhalation        | 32 mg/kg              | Chronic effects systemic |                     |        |
| Workers             | Inhalation        | 151 mg/m <sup>3</sup> | Chronic effects systemic |                     |        |
| Workers             | Dermal            | 12.5 mg/kg bw/day     | Chronic effects systemic |                     |        |
| Consumers           | Dermal            | 7.5 mg/kg bw/day      | Chronic effects systemic |                     |        |
| Consumers           | Oral              | 7.5 mg/kg bw/day      | Chronic effects systemic |                     |        |

**hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

| Workers / consumers | Route of exposure | Value                 | Effect                   | Value determination | Source |
|---------------------|-------------------|-----------------------|--------------------------|---------------------|--------|
| Workers             | Inhalation        | 871 mg/m <sup>3</sup> | Chronic effects systemic |                     |        |
| Consumers           | Inhalation        | 185 mg/m <sup>3</sup> | Chronic effects systemic |                     |        |
| Workers             | Dermal            | 77 mg/kg bw/day       | Chronic effects systemic |                     |        |
| Consumers           | Dermal            | 46 mg/kg bw/day       | Chronic effects systemic |                     |        |
| Consumers           | Oral              | 46 mg/kg bw/day       | Chronic effects systemic |                     |        |

**xylene ( mixture of isomers and ethylbenzene )**

| Workers / consumers | Route of exposure | Value                  | Effect                   | Value determination | Source |
|---------------------|-------------------|------------------------|--------------------------|---------------------|--------|
| Workers             | Inhalation        | 221 mg/m <sup>3</sup>  | Chronic effects systemic |                     |        |
| Workers             | Inhalation        | 442 mg/m <sup>3</sup>  | Acute effects systemic   |                     |        |
| Workers             | Inhalation        | 442 mg/m <sup>3</sup>  | Acute effects local      |                     |        |
| Workers             | Dermal            | 212 mg/kg bw/day       | Chronic effects systemic |                     |        |
| Consumers           | Inhalation        | 65.3 mg/m <sup>3</sup> | Chronic effects systemic |                     |        |
| Consumers           | Inhalation        | 260 mg/m <sup>3</sup>  | Acute effects systemic   |                     |        |
| Consumers           | Inhalation        | 260 mg/m <sup>3</sup>  | Acute effects local      |                     |        |
| Consumers           | Dermal            | 125 mg/kg bw/day       | Chronic effects systemic |                     |        |
| Consumers           | Oral              | 12.5 mg/kg bw/day      | Chronic effects systemic |                     |        |
| Workers             | Inhalation        | 221 mg/m <sup>3</sup>  | Chronic effects local    |                     |        |
| Consumers           | Inhalation        | 65.3 mg/m <sup>3</sup> | Chronic effects local    |                     |        |

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### PNEC

| 2-butanone oxime                   |  |                     |        |
|------------------------------------|--|---------------------|--------|
| Route of exposure                  | Value                                    | Value determination | Source |
| Freshwater environment             | 0.256 mg/l                               |                     |        |
| Water (intermittent release)       | 0.118 mg/l                               |                     |        |
| Microorganisms in sewage treatment | 177 mg/l                                 |                     |        |
| Marine water                       | 0.0256 mg/kg                             |                     |        |
| Freshwater sediment                | 1.012 mg/kg of dry substance of sediment |                     |        |
| Sea sediments                      | 0.101 mg/kg of dry substance of sediment |                     |        |
| Soil (agricultural)                | 0.0522 mg/kg of dry substance of soil    |                     |        |

| 2-ethylhexanoic acid, zirconium salt |  |                     |        |
|--------------------------------------|--|---------------------|--------|
| Route of exposure                    | Value                                    | Value determination | Source |
| Freshwater environment               | 360 µg/l                                 |                     |        |
| Marine water                         | 36 µg/l                                  |                     |        |
| Microorganisms in sewage treatment   | 71.7 mg/l                                |                     |        |
| Freshwater sediment                  | 6.37 mg/kg of dry substance of sediment  |                     |        |
| Sea sediments                        | 0.637 mg/kg of dry substance of sediment |                     |        |
| Soil (agricultural)                  | 1.06 mg/kg of dry substance of soil      |                     |        |

| 2-methoxy-1-methylethyl acetate    |  |                     |        |
|------------------------------------|--|---------------------|--------|
| Route of exposure                  | Value                                    | Value determination | Source |
| Freshwater environment             | 0.635 mg/l                               |                     |        |
| Marine water                       | 0.0635 mg/l                              |                     |        |
| Water (intermittent release)       | 6.35 mg/l                                |                     |        |
| Microorganisms in sewage treatment | 100 mg/l                                 |                     |        |
| Freshwater sediment                | 3.29 mg/kg of dry substance of sediment  |                     |        |
| Sea sediments                      | 0.329 mg/kg of dry substance of sediment |                     |        |

according to Commission Regulation (EU) 2020/878 as amended

**TELKYD T300 E**

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

**2-methoxy-1-methylethyl acetate**

| Route of exposure   | Value                               | Value determination | Source |
|---------------------|-------------------------------------|---------------------|--------|
| Soil (agricultural) | 0.29 mg/kg of dry substance of soil |                     |        |

**calcium bis(2-ethylhexanoate)**

| Route of exposure                  | Value                                    | Value determination | Source |
|------------------------------------|--|---------------------|--------|
| Freshwater environment             | 0.36 mg/l                                |                     |        |
| Marine water                       | 0.036 mg/l                               |                     |        |
| Microorganisms in sewage treatment | 71.7 mg/l                                |                     |        |
| Freshwater sediment                | 6.37 mg/kg of dry substance of sediment  |                     |        |
| Sea sediments                      | 0.637 mg/kg of dry substance of sediment |                     |        |
| Soil (agricultural)                | 1.06 mg/kg of dry substance of soil      |                     |        |

**Cobalt bis(2-ethylhexanoate)**

| Route of exposure                  | Value                                   | Value determination | Source |
|------------------------------------|---|---------------------|--------|
| Freshwater environment             | 0.0062 mg/l                             |                     |        |
| Marine water                       | 0.00236 mg/l                            |                     |        |
| Microorganisms in sewage treatment | 0.37 mg/l                               |                     |        |
| Freshwater sediment                | 53.8 mg/kg of dry substance of sediment |                     |        |
| Sea sediments                      | 69.8 mg/kg of dry substance of sediment |                     |        |
| Soil (agricultural)                | 10.9 mg/kg of dry substance of soil     |                     |        |

**xylene ( mixture of isomers and ethylbenzene )**

| Route of exposure                  | Value                                    | Value determination | Source |
|------------------------------------|--|---------------------|--------|
| Marine water                       | 0.327 mg/l                               |                     |        |
| Water (intermittent release)       | 0.327 mg/l                               |                     |        |
| Microorganisms in sewage treatment | 6.58 mg/l                                |                     |        |
| Freshwater sediment                | 12.46 mg/kg of dry substance of sediment |                     |        |

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

| xylene ( mixture of isomers and ethylbenzene ) |  |                     |        |
|--|--|---------------------|--------|
| Route of exposure                              | Value                                    | Value determination | Source |
| Sea sediments                                  | 12.46 mg/kg of dry substance of sediment |                     |        |
| Soil (agricultural)                            | 2.31 mg/kg of dry substance of soil      |                     |        |
| Freshwater environment                         | 0.327 mg/l                               |                     |        |

### 8.2. Exposure controls

Conditions of safe use of the registered product composition components specified in exposure scenarios to Safety Data Sheets of the components are given in Annex of the SDS, including the required additional measures restricting the exposure – see the exposure scenarios for the intended uses of the product.

General safety and hygienic measures. When working, do not eat, drink, smoke. Before the break and after the work, hands should be washed with soap and hot water, treated with barrier cream. Overall and local ventilation, effective extraction.

#### Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

#### Skin protection

Skin protection: Protective clothes with antistatic finish, protective shoes; treat unprotected skin with barrier cream. Hand protection: Chemical resistant protective gloves (EN 374-1:2003). Suitable material – nitrile rubber (0,4 mm), fluoroelastomere (0,5 mm), PVA (0,7 mm) and others, time of penetration corresponding to > 480 minutes. The time of penetration specified by the manufacturer should be followed and the glove replaced after expiration. If damaged, the gloves should be replaced immediately.

The selection of suitable protective gloves does not only depend on their material, but also on other qualitative features. Furthermore, since the mixture can be used for various purposes, mixed with other substances, the suitability of gloves for all purposes cannot be predetermined and must be verified in particular use.

#### Respiratory protection

Don't breathe vapours. For short-time exposure or low concentration, use respirator with organic vapour and dust filter (protection level A/P2); for high concentration and long-term exposure, self-contained respirator is necessary.

#### Thermal hazard

Not available.

#### Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage. Ensure that containers are properly closed during storage, handling and transport. Secure storage areas against possible leakage of product into the environment (sewerage, water, soil - see 6.2). Do not flush product into drains or watercourses.

#### More information

In the Czech Republic: The monitoring procedure for the content of substances in workplace air and the specification of protective equipment is determined by the worker responsible for occupational safety and health protection of workers. Legal and natural persons doing business have the obligation to measure and control the values of concentrations of substances in the atmosphere of workplaces and to classify workplaces according to the categorization of work.

Exposure scenario is attached to the Safety Data Sheet.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state liquid

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

|  |   |
|--|---|
| Colour   | white, black, red, violet, brown, blue, orange, purple, pink, grey, green, yellow |
| Odour  | typical aromatic  |
| Melting point/freezing point                             | data not available  |
| Boiling point or initial boiling point and boiling range | data not available  |
| Flammability   | Flammable liquid and vapour.  |
| Lower and upper explosion limit                          | data not available  |
| Flash point  | 25 °C (EN ISO 2719)   |
| Auto-ignition temperature                                | data not available  |
| Decomposition temperature                                | data not available  |
| pH   | non-soluble (in water)  |
| Kinematic viscosity                                      | >20.5 mm <sup>2</sup> /s at 40 °C   |
| Solubility in water                                      | not available   |
| Solubility in fats                                       | not available   |
| Partition coefficient n-octanol/water (log value)        | data not available  |
| Vapour pressure  | data not available  |
| Density and/or relative density                          |   |
| Density  | 1.25-1.4 g/cm <sup>3</sup> at 23 °C (EN ISO 2811-1)                               |
| Relative vapour density                                  | data not available  |
| Particle characteristics                                 | data not available  |

### 9.2. Other information

|                                   |  |
|-----------------------------------|--|
| Evaporation rate                  | not available                            |
| Oxidising properties              | The product has no oxidizing properties. |
| Ignition temperature              | >300 °C (EN ISO 14522)                   |
| Content of organic solvents (VOC) | 0.31-0.35 kg/kg                          |
| Total organic carbon (TOC)        | 0.26-0.31 kg/kg                          |
| Solid content (dry matter)        | ≥50 % volume                             |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

When used in the standard way, there is not any dangerous reaction with other substances.

### 10.2. Chemical stability

The product is volatile and evaporates under standard temperature and pressure. It is stable when stored and handled under standard ambient conditions.

### 10.3. Possibility of hazardous reactions

No known dangerous reactions when used under standard conditions. Flammable liquid. Vapours may form explosive mixture with air. Vapours are heavier than air, accumulate near the ground and below ground, and the fire can spread over long distances.

### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

#### Acute toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

| 2-butanone oxime   |                  |        |                   |               |                                  |     |
|--------------------|------------------|--------|-------------------|---------------|----------------------------------|-----|
| Route of exposure  | Parameter        | Method | Value             | Exposure time | Species                          | Sex |
| Oral               | LD <sub>50</sub> |        | 900 mg/kg bw      |               | Rat ( <i>Rattus norvegicus</i> ) |     |
| Inhalation (vapor) | LC <sub>50</sub> |        | >4.83 mg/l of air | 4 hours       | Rat ( <i>Rattus norvegicus</i> ) |     |
| Dermal             | LD <sub>50</sub> |        | 1000 mg/kg bw     |               | Rabbit                           |     |
| Dermal             | ATE              |        | 1100 mg/kg bw     |               |                                  |     |
| Oral               | ATE              |        | 100 mg/kg bw      |               |                                  |     |

| 2-ethylhexanoic acid, zirconium salt |                  |          |                |               |                                  |     |
|--------------------------------------|------------------|----------|----------------|---------------|----------------------------------|-----|
| Route of exposure                    | Parameter        | Method   | Value          | Exposure time | Species                          | Sex |
| Oral                                 | LD <sub>50</sub> | OECD 401 | >5000 mg/kg bw |               | Rat ( <i>Rattus norvegicus</i> ) | F   |
| Dermal                               | LD <sub>50</sub> | OECD 402 | >5000 mg/kg bw |               | Rat ( <i>Rattus norvegicus</i> ) | F/M |

| 2-methoxy-1-methylethyl acetate |                  |        |                          |               |                                  |     |
|---------------------------------|------------------|--------|--------------------------|---------------|----------------------------------|-----|
| Route of exposure               | Parameter        | Method | Value                    | Exposure time | Species                          | Sex |
| Oral                            | LD <sub>50</sub> |        | >5000 mg/kg              |               | Rat ( <i>Rattus norvegicus</i> ) |     |
| Inhalation                      | LC <sub>50</sub> |        | >23500 mg/m <sup>3</sup> | 6 hours       | Rat ( <i>Rattus norvegicus</i> ) |     |
| Dermal                          | LD <sub>50</sub> |        | >5000 mg/kg              |               | Rabbit                           |     |

| calcium bis(2-ethylhexanoate) |                  |          |             |               |                                  |     |
|-------------------------------|------------------|----------|-------------|---------------|----------------------------------|-----|
| Route of exposure             | Parameter        | Method   | Value       | Exposure time | Species                          | Sex |
| Oral                          | LD <sub>50</sub> | OECD 401 | 2043 mg/kg  |               | Rat ( <i>Rattus norvegicus</i> ) | F   |
| Dermal                        | LD <sub>50</sub> | OECD 402 | >5000 mg/kg |               | Rat ( <i>Rattus norvegicus</i> ) | F   |

| Cobalt bis(2-ethylhexanoate) |                  |          |            |               |                                  |     |
|------------------------------|------------------|----------|------------|---------------|----------------------------------|-----|
| Route of exposure            | Parameter        | Method   | Value      | Exposure time | Species                          | Sex |
| Oral                         | LD <sub>50</sub> | OECD 425 | 3129 mg/kg |               | Rat ( <i>Rattus norvegicus</i> ) | F   |

according to Commission Regulation (EU) 2020/878 as amended

**TELKYD T300 E**

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

**Cobalt bis(2-ethylhexanoate)**

| Route of exposure | Parameter        | Method   | Value       | Exposure time | Species                 | Sex |
|-------------------|------------------|----------|-------------|---------------|-------------------------|-----|
| Dermal            | LD <sub>50</sub> | OECD 402 | >2000 mg/kg |               | Rat (Rattus norvegicus) | F/M |

**Hydrocarbons, C10 – C13, n-alkanes, isoalkanes, cyclics, < 2 % aromatics**

| Route of exposure | Parameter        | Method | Value                 | Exposure time | Species                 | Sex |
|-------------------|------------------|--------|-----------------------|---------------|-------------------------|-----|
| Oral              | LD <sub>50</sub> |        | >6000 mg/kg           |               | Rat (Rattus norvegicus) |     |
| Dermal            | LD <sub>50</sub> |        | 3160-5000 mg/kg bw    |               | Rabbit                  |     |
| Inhalation        | LC <sub>50</sub> |        | 4.951-9.3 mg/l of air | 4 hours       | Rat (Rattus norvegicus) |     |

**hydrocarbons, C9, aromatics**

| Route of exposure | Parameter        | Method | Value                  | Exposure time | Species                 | Sex |
|-------------------|------------------|--------|------------------------|---------------|-------------------------|-----|
| Oral              | LD <sub>50</sub> |        | 3492 mg/kg             |               | Rat (Rattus norvegicus) |     |
| Dermal            | LD <sub>50</sub> |        | 3160 mg/kg             |               | Rabbit                  |     |
| Inhalation        | LC <sub>50</sub> |        | 6193 mg/m <sup>3</sup> | 4 hours       | Rat (Rattus norvegicus) |     |

**hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

| Route of exposure | Parameter        | Method   | Value       | Exposure time | Species                 | Sex |
|-------------------|------------------|----------|-------------|---------------|-------------------------|-----|
| Oral              | LD <sub>50</sub> | OECD 401 | >5000 mg/kg |               | Rat (Rattus norvegicus) |     |
| Dermal            | LD <sub>50</sub> | OECD 402 | >5000 mg/kg |               | Rat (Rattus norvegicus) |     |

**xylene ( mixture of isomers and ethylbenzene )**

| Route of exposure  | Parameter        | Method | Value          | Exposure time | Species                 | Sex |
|--------------------|------------------|--------|----------------|---------------|-------------------------|-----|
| Oral               | LD <sub>50</sub> | EU B.1 | 3523 mg/kg bw  |               | Rat (Rattus norvegicus) | M   |
| Dermal             | LD <sub>50</sub> |        | 12126 mg/kg bw |               | Rabbit                  |     |
| Inhalation (vapor) | LC <sub>50</sub> |        | 6350-6700 ppm  | 4 hours       | Rat (Rattus norvegicus) | M   |

**Skin corrosion/irritation**

Causes skin irritation. Data for the components of the mixture are not available.

**Serious eye damage/irritation**

Causes serious eye irritation. Data for the components of the mixture are not available.

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### Respiratory or skin sensitisation

May cause an allergic skin reaction. Data for the components of the mixture are not available.

### Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

### Carcinogenicity

May cause cancer. Data for the components of the mixture are not available.

### Reproductive toxicity

May damage the unborn child. Data for the components of the mixture are not available.

### Toxicity for specific target organ - single exposure

May cause respiratory irritation. Data for the components of the mixture are not available.

### Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure. Data for the components of the mixture are not available.

### Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

## 11.2. Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 12: Ecological information

### 12.1. Toxicity

Harmful to aquatic life with long lasting effects.

#### Acute toxicity

| 2-butanone oxime                     |          |           |               |   |             |
|--------------------------------------|----------|-----------|---------------|---|-------------|
| Parameter                            | Method   | Value     | Exposure time | Species                                     | Environment |
| LC <sub>50</sub>                     |          | >100 mg/l | 96 hours      | Fish (Oncorhynchus mykiss)                  |             |
| EC <sub>50</sub>                     |          | 201 mg/l  | 48 hours      | Aquatic invertebrates                       |             |
| EC <sub>50</sub>                     |          | 11.8 mg/l | 72 hours      | Algae and other aquatic plants              |             |
| EC <sub>50</sub>                     |          | 281 mg/l  | 17 hours      | Microorganisms (Photobacterium phosphoreum) |             |
| 2-ethylhexanoic acid, zirconium salt |          |           |               |   |             |
| Parameter                            | Method   | Value     | Exposure time | Species                                     | Environment |
| LC <sub>50</sub>                     | OECD 203 | >100 mg/l | 96 hours      | Fish (Oryzias latipes)                      |             |

according to Commission Regulation (EU) 2020/878 as amended

**TELKYD T300 E**

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

**2-ethylhexanoic acid, zirconium salt**

| Parameter | Method   | Value   | Exposure time | Species                 | Environment |
|-----------|----------|---------|---------------|-------------------------|-------------|
| NOEC      | OECD 211 | 25 mg/l | 21 days       | Daphnia (Daphnia magna) | Fresh water |

**2-methoxy-1-methylethyl acetate**

| Parameter         | Method | Value      | Exposure time | Species                        | Environment |
|-------------------|--------|------------|---------------|--------------------------------|-------------|
| LC <sub>50</sub>  |        | 134 mg/l   | 96 hours      | Fish (Oncorhynchus mykiss)     |             |
| EC <sub>50</sub>  |        | 408 mg/l   | 48 hours      | Daphnia (Daphnia magna)        |             |
| ErC <sub>50</sub> |        | >1000 mg/l | 96 hours      | Algae and other aquatic plants |             |

**calcium bis(2-ethylhexanoate)**

| Parameter        | Method   | Value      | Exposure time | Species  | Environment |
|------------------|----------|------------|---------------|--|-------------|
| EC <sub>50</sub> | OECD 203 | >100 mg/l  | 96 hours      | Fish (Oryzias latipes)                           |             |
| EC <sub>50</sub> |          | 49.3 mg/l  | 96 hours      | Algae and other aquatic plants (Desmodesmus sp.) |             |
| EC <sub>50</sub> |          | 112.1 mg/l | 17 hours      | Microorganisms (Photobacterium phosphoreum)      |             |
| EC <sub>50</sub> | OECD 202 | 85.4 mg/l  | 48 hours      | Daphnia (Daphnia magna)                          |             |

**Cobalt bis(2-ethylhexanoate)**

| Parameter        | Method | Value       | Exposure time | Species                    | Environment |
|------------------|--------|-------------|---------------|----------------------------|-------------|
| LC <sub>50</sub> |        | 41.6 mg/l   | 28 days       | Fish (Oncorhynchus mykiss) |             |
| EC <sub>10</sub> |        | 0.0197 mg/l | 7 days        | Aquatic invertebrates      |             |

**hydrocarbons, C9, aromatics**

| Parameter         | Method | Value    | Exposure time | Species                                 | Environment |
|-------------------|--------|----------|---------------|---|-------------|
| LL <sub>50</sub>  |        | 9.2 mg/l | 96 hours      | Fish (Oncorhynchus mykiss)              |             |
| EL <sub>50</sub>  |        | 3.2 mg/l | 48 hours      | Daphnia (Daphnia magna)                 |             |
| ErL <sub>50</sub> |        | 2.9 mg/l | 72 hours      | Algae (Pseudokirchneriella subcapitata) |             |

according to Commission Regulation (EU) 2020/878 as amended

**TELKYD T300 E**

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

**hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

| Parameter        | Method   | Value        | Exposure time | Species                                 | Environment |
|------------------|----------|--------------|---------------|---|-------------|
| EC <sub>50</sub> | OECD 201 | >1000 mg/l   | 72 hours      | Algae (Pseudokirchneriella subcapitata) |             |
| EC <sub>50</sub> | OECD 202 | 22-46 mg/l   | 48 hours      | Daphnia (Daphnia magna)                 |             |
| IC <sub>50</sub> | OECD 203 | >10-<30 mg/l | 48 hours      | Fish (Oncorhynchus mykiss)              |             |

**xylene ( mixture of isomers and ethylbenzene )**

| Parameter        | Method | Value    | Exposure time | Species                                 | Environment |
|------------------|--------|----------|---------------|---|-------------|
| LC <sub>50</sub> |        | 2.6 mg/l | 96 hours      | Fish (Oncorhynchus mykiss)              |             |
| EC <sub>50</sub> |        | 1 mg/l   | 48 hours      | Daphnia (Daphnia magna)                 |             |
| LC <sub>50</sub> |        | 2.2 mg/l | 72 hours      | Algae (Pseudokirchneriella subcapitata) |             |

**Chronic toxicity**
**xylene ( mixture of isomers and ethylbenzene )**

| Parameter | Value          | Exposure time | Species                            | Environment |
|-----------|----------------|---------------|------------------------------------|-------------|
| NOEC      | >1.3 mg/l      | 56 days       | Fish (Oncorhynchus mykiss)         |             |
| NOEC      | 0.96-1.17 mg/l | 7 days        | Invertebrates (Ceriodaphnia dubia) |             |

**12.2. Persistence and degradability**

Data for the mixture are not available.

**Biodegradability**
**hydrocarbons, C9, aromatics**

| Parameter | Method | Value | Exposure time | Environment | Result               |
|-----------|--------|-------|---------------|-------------|----------------------|
|           |        |       |               |             | Easily biodegradable |

**xylene ( mixture of isomers and ethylbenzene )**

| Parameter | Method    | Value | Exposure time | Environment | Result               |
|-----------|-----------|-------|---------------|-------------|----------------------|
|           | OECD 301F | >90 % | 28 days       |             | Easily biodegradable |

**12.3. Bioaccumulative potential**

Data for the mixture are not available.

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### 2-butanone oxime

| Parameter | Value | Exposure time | Species | Environment | Temperature [°C] |
|-----------|-------|---------------|---------|-------------|------------------|
| Log Pow   | 0.63  |               |         |             |                  |

### 2-methoxy-1-methylethyl acetate

| Parameter | Value | Exposure time | Species | Environment | Temperature [°C] |
|-----------|-------|---------------|---------|-------------|------------------|
| BCF       | <100  |               |         |             |                  |
| Log Pow   | <3    |               |         |             |                  |

### xylene ( mixture of isomers and ethylbenzene )

| Parameter | Value    | Exposure time | Species | Environment | Temperature [°C] |
|-----------|----------|---------------|---------|-------------|------------------|
| Log Pow   | 3.12-3.2 |               |         |             |                  |
| BCF       | 6-23.4   |               |         |             |                  |

#### 12.4. Mobility in soil

The mixture is a liquid insoluble in water, in case of leakage into environment, it may be dispersed over large distances and penetrate into underground water. It contains components with the potential of mobility in soil. When released into the soil may occur due to contamination of groundwater.

### 2-methoxy-1-methylethyl acetate

| Parameter | Value | Environment | Temperature |
|-----------|-------|-------------|-------------|
| Koc       | 1.7   |             |             |

### xylene ( mixture of isomers and ethylbenzene )

| Parameter | Value  | Environment | Temperature |
|-----------|--------|-------------|-------------|
| Koc       | 48-540 |             |             |

#### 12.5. Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

#### 12.6. Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

#### 12.7. Other adverse effects

Volatile organic substances contained in the mixture have the potential to damage ozone layer.

### SECTION 13: Disposal considerations

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### 13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

#### Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

#### Waste type code

08 01 11 waste paint and varnish containing organic solvents or other hazardous substances \*

#### Packaging waste type code

15 01 10 packaging containing residues of or contaminated by hazardous substances \*

(\* ) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

## SECTION 14: Transport information

### 14.1. UN number or ID number

UN 1263

### 14.2. UN proper shipping name

PAINT

### 14.3. Transport hazard class(es)

3 Flammable liquids

### 14.4. Packing group

III - substances presenting low danger

### 14.5. Environmental hazards

not relevant

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

Not classified.

#### Additional information

Hazard identification No.

30

UN number

1263

Classification code

F1

Safety signs

3



according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

**Air transport - ICAO/IATA**

|                                  |     |
|----------------------------------|-----|
| Packaging instructions passenger | 355 |
| Cargo packaging instructions     | 366 |

**Marine transport - IMDG**

|                      |          |
|----------------------|----------|
| EmS (emergency plan) | F-E, S-E |
| MFAG                 | 310      |

**SECTION 15: Regulatory information**
**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

**Restrictions pursuant to Annex XVII of Regulation (EC) No. 1907/2006 (REACH), as amended**

2-ethylhexanoic acid, zirconium salt, Cobalt bis(2-ethylhexanoate)

| Restriction | Conditions of restriction   |
|-------------|---|
| 30          | <p>Without prejudice to the other parts of this Annex the following shall apply to entries 28 to 30:</p> <p>1. Shall not be placed on the market, or used,</p> <ul style="list-style-type: none"> <li>– as substances,</li> <li>– as constituents of other substances, or,</li> <li>– in mixtures, for supply to the general public when the individual concentration in the substance or mixture is equal to or greater than:                             <ul style="list-style-type: none"> <li>– either the relevant specific concentration limit specified in Part 3 of Annex VI to Regulation (EC) No 1272/2008, or,</li> <li>– the relevant generic concentration limit specified in Part 3 of Annex I of Regulation (EC) No 1272/2008.</li> </ul> </li> </ul> <p>Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of such substances and mixtures is marked visibly, legibly and indelibly as follows:</p> <p>“Restricted to professional users”.</p> <p>2. By way of derogation, paragraph 1 shall not apply to:</p> <ul style="list-style-type: none"> <li>(a) medicinal or veterinary products as defined by Directive 2001/82/EC and Directive 2001/83/EC;</li> <li>(b) cosmetic products as defined by Directive 76/768/EEC;</li> <li>(c) the following fuels and oil products:                             <ul style="list-style-type: none"> <li>– motor fuels which are covered by Directive 98/70/EC,</li> <li>– mineral oil products intended for use as fuel in mobile or fixed combustion plants,</li> <li>– fuels sold in closed systems (e.g. liquid gas bottles);</li> </ul> </li> <li>(d) artists’ paints covered by Regulation (EC) No 1272/2008;</li> <li>(e) the substances listed in Appendix 11, column 1, for the applications or uses listed in Appendix 11, column 2. Where a date is specified in column 2 of Appendix 11, the derogation shall apply until the said date.</li> <li>(f) devices covered by Regulation (EU) 2017/745.</li> </ul> |

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### 15.2. Chemical safety assessment

Chemical safety assessment was carried out on the individual substances of the mixture. The respective exposure scenarios are incorporated in Annex of this Safety Data Sheet.

### SECTION 16: Other information

#### A list of standard risk phrases used in the safety data sheet

|           |  |
|-----------|--|
| H226      | Flammable liquid and vapour.   |
| H301      | Toxic if swallowed.  |
| H304      | May be fatal if swallowed and enters airways.                            |
| H312      | Harmful in contact with skin.  |
| H315      | Causes skin irritation.  |
| H317      | May cause an allergic skin reaction.                                     |
| H318      | Causes serious eye damage.   |
| H319      | Causes serious eye irritation.   |
| H335      | May cause respiratory irritation.  |
| H336      | May cause drowsiness or dizziness.                                       |
| H350      | May cause cancer.  |
| H360D     | May damage the unborn child.   |
| H360FD    | May damage fertility. May damage the unborn child.                       |
| H370      | Causes damage to upper respiratory tract.                                |
| H373      | May cause damage to blood system through prolonged or repeated exposure. |
| H373      | May cause damage to organs through prolonged or repeated exposure.       |
| H400      | Very toxic to aquatic life.  |
| H411      | Toxic to aquatic life with long lasting effects.                         |
| H412      | Harmful to aquatic life with long lasting effects.                       |
| H312+H332 | Harmful in contact with skin or if inhaled.                              |

#### Guidelines for safe handling used in the safety data sheet

|           |  |
|-----------|--|
| P201      | Obtain special instructions before use.  |
| P210      | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P261      | Avoid breathing vapours/spray.   |
| P264      | Wash hands and exposed parts of the body thoroughly after handling.                            |
| P280      | Wear protective gloves/protective clothing/eye protection.                                     |
| P308+P313 | IF exposed or concerned: Get medical advice/attention.   |
| P312      | Call a doctor if you feel unwell.  |

#### A list of additional standard phrases used in the safety data sheet

|        |   |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
|--------|---|

#### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

#### Key to abbreviations and acronyms used in the safety data sheet

|     |   |
|-----|---|
| ADR | European agreement concerning the international carriage of dangerous goods by road               |
| BCF | Bioconcentration Factor   |
| CAS | Chemical Abstracts Service  |
| CLP | Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures |
| EC  | Identification code for each substance listed in EINECS   |

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

|                     |   |
|---------------------|---|
| EC <sub>10</sub>    | Concentration of a substance when it is affected 10% of the population                            |
| EC <sub>50</sub>    | Concentration of a substance when it is affected 50% of the population                            |
| EINECS              | European Inventory of Existing Commercial Chemical Substances                                     |
| EL <sub>50</sub>    | Effective Loading for 50% of the tested organisms   |
| EmS                 | Emergency plan  |
| EU                  | European Union  |
| EuPCS               | European Product Categorisation System  |
| IATA                | International Air Transport Association   |
| IBC                 | International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals       |
| IC <sub>50</sub>    | Concentration causing 50% blockade  |
| ICAO                | International Civil Aviation Organization   |
| IMDG                | International Maritime Dangerous Goods  |
| IMO                 | International Maritime Organization   |
| INCI                | International Nomenclature of Cosmetic Ingredients  |
| ISO                 | International Organization for Standardization  |
| IUPAC               | International Union of Pure and Applied Chemistry   |
| LC <sub>50</sub>    | Lethal concentration of a substance in which it can be expected death of 50% of the population    |
| LD <sub>50</sub>    | Lethal dose of a substance in which it can be expected death of 50% of the population             |
| LL <sub>50</sub>    | Lethal Loading for 50% of tested organisms  |
| log K <sub>ow</sub> | Octanol-water partition coefficient   |
| NOEC                | No observed effect concentration  |
| OEL                 | Occupational Exposure Limits  |
| PBT                 | Persistent, Bioaccumulative and Toxic   |
| ppm                 | Parts per million   |
| REACH               | Registration, Evaluation, Authorisation and Restriction of Chemicals                              |
| RID                 | Agreement on the transport of dangerous goods by rail   |
| UN                  | Four-figure identification number of the substance or article taken from the UN Model Regulations |
| UVCB                | Substances of unknown or variable composition, complex reaction products or biological materials  |
| VOC                 | Volatile organic compounds  |
| vPvB                | Very Persistent and very Bioaccumulative  |
| Acute Tox.          | Acute toxicity  |
| Aquatic Acute       | Hazardous to the aquatic environment  |
| Aquatic Chronic     | Hazardous to the aquatic environment (chronic)  |
| Asp. Tox.           | Aspiration hazard   |
| Carc.               | Carcinogenicity   |
| Eye Dam.            | Serious eye damage  |
| Flam. Liq.          | Flammable liquid  |
| Repr.               | Reproductive toxicity   |
| Skin Irrit.         | Skin irritation   |
| Skin Sens.          | Skin sensitization  |
| STOT RE             | Specific target organ toxicity - repeated exposure  |
| STOT SE             | Specific target organ toxicity - single exposure  |

according to Commission Regulation (EU) 2020/878 as amended

## TELKYD T300 E

|               |                     |         |     |
|---------------|---------------------|---------|-----|
| Creation date | 03rd August 2016    | Version | 5.0 |
| Revision date | 25th September 2023 |         |     |

### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### Recommended restrictions of use

The product is exclusively intended for use in installations authorised according to Directive 1999/13/EC where emission limiting measures provide alternative means of achieving at least equivalent VOC emission reductions. For professional use only.

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.  
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### The changes (which information has been added, deleted or modified)

The version 5.0 replaces the SDS version from 7.2.2022. Overall revision of SDS.

### Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

## Annex to the Product Safety Data Sheet - EXPOSURE SCENARIO RECOMMENDATION ON SAFE USE OF THE MIXTURE

### 1. Industrial use

|   |  |
|---|--|
| Application sector                              | : SU 3   |
| Chemical product category                       | : PC9a   |
| Partial processes covered by exposure scenario: | PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15 |
| Environmental release                           | : ERC4   |

#### Basic conditions to control the hazard for workers:

|   |  |
|---|--|
| Duration of work activities             | : Covers exposure up to 8 h/d (unless otherwise specified)   |
| Concentration                           | : Work with standard coating composition or coating composition thinned by solvents containing the same volatile components as the coating composition is anticipated.   |
| Temperature                             | : Work at temperature up to 20 °C higher than site temperature is anticipated except for the coating composition's drying and hardening processes at increased temperature.  |
| General risk management measures        | : Wear protective working clothes. Wear protective gloves and eye protection if in danger of contact with the coating composition (see section 8.2. of the SDS). Basic training required.<br>: Use respiratory protection if NPK or PEL values are exceeded (see section 8 of the SDS).<br>: Abide by general principles of safe and hygienic work with chemical substances.<br>: Workplaces must meet the requirements for work with flammable liquids capable of producing explosive mixtures of vapours with air.<br>: The workplace must meet the requirements against accidental leaks of the product into water or soil. |
| Site where the activities are performed | : Indoor use is anticipated.   |

#### Additional requirements to control the hazard for workers carrying out partial work activities:

| Partial work activities with the product (Partial contributing scenarios)  | Process category  | Required additional measures to control worker exposure  |
|--|---|--|
| Pumping from/to containers and devices within a closed system with no possibility to release emission  | PROC 1 Use within closed production process   | Does not require further risk control measures.  |
| Pumping the coating composition from/to containers and devices at non dedicated facility with potential human and environment exposure               | PROC 8a Transfer of the product (charging / discharging) to/from vessels/large containers at non dedicated facilities | Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).   |
| Pumping the coating composition from/to containers and devices at non dedicated facility with potential human and environment exposure               | PROC 8b Transfer of the product (charging / discharging) to/from vessels/large containers at dedicated facilities     | Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).   |
| Mixing, blending, thinning of coating composition in open devices with possible exposure to volatile components of the coating composition           | PROC5 Mixing or blending in batch processes at mixture manufacturing (excl. charging and discharging of vessels).     | Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).   |
| Application by spraying.   | PROC 7 Industrial spraying.   | Robotic spraying in closed chambers or closed cabs with laminar extraction. In course of spraying, enter the chambers only with self-contained respirator.<br>Manual spraying in spraying chambers with laminar flow of extracted air directed from the worker or in intensively ventilated spaces (5-10 air exchanges per hour) with respiratory protection (half-face or full-face respirator) provided with type A/P2 filter. |
| Manual coating composition application by roller, brush or palette knife.  | PROC 10 Roller, palette knife or brush application  | Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).   |
| Dipping or pouring application of coating composition.   | PROC 13 Treatment of articles by dipping and pouring  | Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).   |
| Free drying of coating composition film at standard or slightly increased ambient temperature (by max. 20 °C)  | PROC 4 Use within batch or other process where opportunity for exposure arises  | Carry out in well ventilated spaces (3-5 air exchanges per hour).  |
| Continuous drying and hardening processes of the coating composition film at increased temperature in drying tunnels equipped with vapour extraction | PROC 2 Use within continuous chemical production process with occasional controlled exposure (e.g. at sampling).      | Does not require further risk control measures.  |
| Batch drying and hardening processes of the coating composition film at increased temperature in extracted chambers                                  | PROC 3 Use within closed batch process of mixture manufacturing.  | Does not require further risk control measures.  |

|  |  |   |
|--|--|---|
| Machine cleaning and washing of closed tanks, containers and devices equipped with vapour extraction | PROC 3 Use within closed batch process of mixture manufacturing  | Does not require further risk control measures.   |
| Manual cleaning of small containers, application devices and tools                                   | PROC 10 Roller or brush application (by a tool held in hand)<br>PROC8a Transfer of the product (charging / discharging) to/from vessels/large containers at non dedicated facilities | Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).  |
| Laboratory checks on the coating composition   | PROC 15 Use as laboratory reagent (laboratory work with the product)   | Handling in a fume hood or in the presence of vacuum ventilation.   |
| Activities involving product waste and waste contaminated by the product                             |  | If in risk of contact with waste, wear protective gloves. Store the waste in closable containers stored in well ventilated storages or outdoor. |

#### Additional requirements to control environmental hazards

|                        |  |
|------------------------|--|
| Air emission control   | When spraying, remove fly coating mist from the air extracted from the work site. If the limits for solvent consumption defined in Ordinance no. 415/2012 Coll. are exceeded, use solvent recuperation from waste air or remove the solvents by incineration or other processes guaranteeing observation of emission parameters specified in air protection regulations.   |
| Water emission control | Store the coating and waste contaminated by coat in buildings structurally protected from leakage release and emergency release to surface and ground water.<br>Treat water contaminated by coat compounds and remove solid impurities and organic compounds by sedimentation, filtration, biological treatment processes or special processes developed for treatment of water contaminated by coating compositions before discharging to surface water.<br>When discharging the treated waste water, observe the contamination parameters specified for the involved facility by water management authority. |
| Disposal of waste      | Dispose of coat waste and materials contaminated by coat and its compounds in cooperation with authorised persons as of hazardous waste.<br>Dispose of solvent waste from tools and device cleaning as of hazardous waste.<br>Prevent release or discharge of any liquid waste to surface and ground water unless it is treated and coating composition compounds are removed.   |

## 2. Professional use

|   |   |
|---|---|
| Application sector                              | : SU 22   |
| Chemical product category                       | : PC9a  |
| Partial processes covered by exposure scenario: | PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19 |
| Environmental release                           | : ERC 8a, ERC 8d  |

#### Basic conditions to control the hazard for workers:

|   |  |
|---|--|
| Duration of work activities             | : Covers exposure up to 8 h/d (unless otherwise specified)   |
| Concentration                           | : Work with standard coating composition or coating composition thinned by solvents containing the same volatile components as the coating composition is anticipated.   |
| Temperature                             | : Work at temperature up to 20 °C higher than site temperature is anticipated except for the coating composition's drying and hardening processes at increased temperature.  |
| General risk management measures        | : Wear protective working clothes. Wear protective gloves and eye protection if in danger of contact with the coating composition (see section 8.2. of the SDS). Basic training required.<br>: Use respiratory protection if NPK or PEL values are exceeded (see section 8 of the SDS).<br>: Abide by general principles of safe and hygienic work with chemical substances.<br>: Workplaces must meet the requirements for work with flammable liquids capable of producing explosive mixtures of vapours with air.<br>: The workplace must meet the requirements against accidental leaks of the product into water or soil. |
| Site where the activities are performed | : Indoor and outdoor use is anticipated.   |

#### Additional requirements to control the hazard for workers carrying out partial work activities:

| Partial work activities with the product (Partial contributing scenarios)  | Process category  | Required additional measures to control worker exposure  |
|--|---|--|
| Pumping the coating composition from/to containers and devices at non dedicated facility with potential human and environment exposure | PROC 8a Transfer of the product (charging / discharging) to/from vessels/large containers at non dedicated facilities | Indoor: local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).<br>Outdoor: secure catch dripping paint |

|  |   |  |
|--|---|--|
| Pumping the coating composition from/to containers and devices at non dedicated facility with potential human and environment exposure     | PROC 8b Transfer of the product (charging / discharging) to/from vessels/large containers at dedicated facilities | Indoor: local air extraction at potential emission release or good ventilation (5-10 air exchanges per hour).<br>Outdoor: does not require further risk control measures   |
| Mixing, blending, thinning of coating composition in open devices with possible exposure to volatile components of the coating composition | PROC5 Mixing or blending in batch processes at mixture manufacturing (excl. charging and discharging of vessels). | Indoor: local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).<br>Outdoor: working process a maximum of 4h per day does not require further risk control measures or use respiratory protection with filter type A.  |
| Application by spraying.   | PROC 11 Non industrial spraying.  | Indoor: do spraying in spraying chambers with laminar flow of extracted air directed from the worker or in intensively ventilated spaces (5-10 air exchanges per hour) with respiratory protection (half-face or full-face respirator) provided with type A/P2 filter.<br>Outdoor: use respiratory protection with filter type A/P2. |
| Manual coating composition application by roller, brush or palette knife.  | PROC 10 Roller, palette knife or brush application  | Indoor: local air extraction at potential emission release or good ventilation (5-10 air exchanges per hour).<br>Outdoor: does not require further risk control measures   |
| Dipping or pouring application of coating composition.   | PROC 13 Treatment of articles by dipping and pouring  | Indoor: local air extraction at potential emission release or good ventilation (5-10 air exchanges per hour).<br>Outdoor: use respiratory protection with filter type A.   |
| Free drying of coating composition film at standard or slightly increased ambient temperature (by max. 20 °C)                              | PROC 4 Use within batch or other process where opportunity for exposure arises                                    | Indoor: carry out in well ventilated spaces (5--10 air exchanges per hour).<br>Outdoor: does not require further risk control measures   |
| Batch drying and hardening processes of the coating composition film at increased temperature in extracted chambers                        | PROC 3 Use within closed batch process of mixture manufacturing.  | Does not require further risk control measures.  |
| Manual cleaning of small containers, application devices and tools   | PROC 10 Roller or brush application (by a tool held in hand)  | Indoor: local air extraction at potential emission release or good ventilation (5-10 air exchanges per hour).<br>Outdoor: does not require further risk control measures   |
| Laboratory checks on the coating composition   | PROC 15 Use as laboratory reagent (laboratory work with the product)  | Handling in a fume hood or in the presence of vacuum ventilation.  |
| Manual activities involving hand contact   | PROC19 Hand-mixing with intimate contact and only PPE available   | Indoor. Use protective gloves, local air extraction at potential emission release or good ventilation<br>Outdoor: use protective gloves  |
| Activities involving product waste and waste contaminated by the product   |   | If in risk of contact with waste, wear protective gloves. Store the waste in closable containers stored in well ventilated storages or outdoor.  |

#### Additional requirements to control environmental hazards

|                        |  |
|------------------------|--|
| Air emission control   | Does not require special risk control measures   |
| Water emission control | Store the paints and waste contaminated by paints in buildings structurally protected from leakage release and emergency release to surface and ground water.<br>Clean up waste water contaminated by paints in the Municipal wastewater treatment plants before discharging to surface water or capture or dispose them as hazardous waste in cooperation with the authorized person.<br>Overspray and drips paint as possible to capture and dispose as hazardous waste. |
| Disposal of waste      | Prevent leakage or discharge of any liquid waste into surface and groundwater unless it is cleaned up from the paint compounds.<br>Dispose of paint waste and materials contaminated by paints and its compounds in cooperation with authorised persons as of hazardous waste.<br>Dispose of solvent waste from tools and device cleaning as of hazardous waste.   |