

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Substance / mixture	TELPOX P100 S
UFI	mixture CV9W-202H-A002-JGRM

1.2. Relevant identified uses of the substance or mixture and uses advised against
Mixture's intended use

TWO COMPONENT EPOXY ANTICORROSIVE PRIMER. For professional use only.

Mixture uses advised againstThe product should not be used in ways other than those referred in Section 1.
Exposure scenario is attached to the Safety Data Sheet.**1.3. Details of the supplier of the safety data sheet****Manufacturer**

Name or trade name	BARVY A LAKY TELURIA,s.r.o.
Address	Č.p.1, Skrchov, 679 61 Czech Republic
Identification number (CRN)	43420371
VAT number	CZ43420371
Phone	+420 516 474 211
Email	info@teluria.cz
Web address	http://www.bal.cz

Competent person responsible for the safety data sheet

Name	BARVY A LAKY TELURIA,s.r.o.
Email	info@teluria.cz

1.4. Emergency telephone number

European emergency number: 112

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Flam. Liq. 3, H226
Skin Irrit. 2, H315
Skin Sens. 1, H317
Eye Dam. 1, H318
STOT SE 3, H335
STOT RE 2, H373
Aquatic Chronic 2, H411**Most serious adverse physico-chemical effects**

Flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May cause damage to organs through prolonged or repeated exposure. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. Toxic to aquatic life with long lasting effects.

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

2.2. Label elements

Hazard pictogram



Signal word

Danger

Hazardous substances

xylene (mixture of isomers and ethylbenzene)

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight 700-1100) butan-1-ol

Hazard statements

H226	Flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a doctor.

Supplemental information

Density	1.33 g/cm ³ at 20 °C (hardened mixture)
VOC	0,37 kg/kg
TOC	0,31 kg/kg
Dry matter	47 % volume
VOC limit value	cat. A (j) SB: 500 g/l

2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components. Substances are neither listed in Annex XIV of REACH nor on the REACH candidate list of substances of very high concern (SVHC).

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date 25th January 2018 Version 5.0
Revision date 03rd June 2026

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of inorganic pigments and fillers in solution of medium molecular epoxy resin in organic solvents with addition of additives and Zn phosphate.

The mixture contains a reaction mixture of o, m, p-xylene and ethylbenzene (ethylbenzene content <26%).

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 14807-96-6 EC: 238-877-9	talca (Mg ₃ H ₂ (SiO ₃) ₄)	28-30	not classified as dangerous	
EC: 905-562-9 Registration number: 01-2119555267-33	xylene (mixture of isomers and ethylbenzene)	21.4-27.1	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373	1, 2
Index: 603-074-00-8 CAS: 25068-38-6 EC: 500-033-5 Registration number: polymer	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight 700-1100)	18.9-21.6	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Specific concentration limit: Skin Irrit. 2, H315; Eye Irrit. 2, H319: C ≥ 5 %	
Index: 603-004-00-6 CAS: 71-36-3 EC: 200-751-6	butan-1-ol	8	Flam. Liq. 3, H226 Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336	
CAS: 1317-65-3 EC: 215-279-6	limestone	5-10	not classified as dangerous	
Index: 030-011-00-6 CAS: 7779-90-0 EC: 231-944-3 Registration number: 01-21194850-44-40-0001	trizinc bis(orthophosphate)	2.5	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	
CAS: 1302-78-9 EC: 215-108-5	bentonite dust	2	not classified as dangerous	
Index: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6 Registration number: 01-2119457610-43	ethanol	1	Flam. Liq. 2, H225 Eye Irrit. 2, H319	

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

Notes

- 1 *Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.*
- 2 *A substance for which exposure limits are set.*

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

DO NOT INDUCE VOMITING! Rinse out the mouth with water and provide 2-5 dL of water. Provide medical treatment if the person has any health problems.

4.2. Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system. May cause respiratory irritation.

If on skin

May cause an allergic skin reaction.

If in eyes

Causes serious eye damage.

If swallowed

Corrosion of the digestion system can occur.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment. If you see a doctor, take this safety data sheet with you.

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For workers apart from emergency teams: Avoid inhalation of vapour, prevent skin and eye contact. Wear appropriate protective clothing and gloves. Wear eye protection and face shield if necessary. Use suitable respiratory protection. In closed spaces, ensure fresh air supply. Eliminate all ignition sources. No smoking and no open fire. Keep unnecessary personnel away.

For members of emergency teams: Use appropriate personal protective equipment – protective clothing with antistatic finish and impermeable work shoes. Treat unprotected skin with barrier cream. Anti-chemical protective gloves. For short-time exposure or low concentration, use respirator with organic vapour and dust filter (protection level A/P2); for high concentration and long-term exposure, self-contained respirator is necessary.

6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water. If possible prevent leakage, close container and place damaged container in protective container. Do not allow to enter drains.

6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4. Reference to other sections

See the Section 7, 8 and 13.

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

SECTION 7: Handling and storage**7.1. Precautions for safe handling****7.1.1. General health measures**

Use the product after due familiarization with its hazard characteristics and proper training or training in its safe use. Do not eat, drink, smoke on the site. Wash your hands and other contaminated parts of body by soap and water before eating and after the use of product is finished. Abide by requirements on personal hygiene when working with hazardous chemical products.

Use technical equipment on the site to control human and environment exposure. Regularly inspect the equipment, ensure cleaning, timely maintenance and permanent functionality. When working, use the recommended personal protective equipment listed in 8.2 of the Safety Data Sheet and in Annex to the Safety Data Sheet. Keep the protective clothing and protective equipment sound and clean. Immediately replace the damaged protective aids for sound ones. Keep the site, tools and aids clean and in sound state. On the site, keep the product in labelled containers or tanks. Store product waste and wastes contaminated by the product in suitable and properly labelled vessels located on designated marked and protected places. Ensure long-term storing of wastes containing the product outside the site.

7.1.2. Fire precautions

When using the product, prevent potential ignition or explosion of the mixture of product vapour and air caused by contact with open flame, sparks, extremely hot surfaces, electrostatic discharges. Do not smoke on the site, use non-sparking tools. Places with increased occurrence of the vapour-air mixture need to be ventilated to prevent formation of explosive mixtures. Solvent vapours are heavier than air. The site should be protected from electrostatic discharges.

7.1.3. Environmental precautions

Handle the product on a site technically adapted to avoid accidental leakage to sewerage systems, water or soil. Product waste and wastes contaminated by the product to be disposed of as hazardous waste. Waste water contaminated by the product may only be discharged to water reservoirs after the product components are properly removed in a waste water treatment plant or in other appropriate treatment plant able to remove drifted product components from water. Do not pour the product to waste water. Emissions of solvent from point sources are subjected to control requirements acc. to air protection regulations.

7.2. Conditions for safe storage, including any incompatibilities

Store the product in properly marked, closed containers in well ventilated spaces at 5 – 25 °C. The storages must meet the requirements on storing of flammable liquids and substances hazardous for aquatic life and soil. Protect from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. Store away from oxidising substances and strong acids. Do not store with food, drinks, feed material, medicines. Storages should be protected from static electricity. First aid kit and water suitable for eye rinsing should be available. Keep away from products that are corrosive to metals (eg acids or pool chemicals).

Storage class

3A - Flammable liquids (flash point below 55 °C)

Storage temperature

min 5 °C, max 25 °C

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3. Specific end use(s)

Use in coating compositions was assessed for all of substances except epoxy resin. Conditions of safe use of the registered coating composition components specified in exposure scenarios to SDSs of the components are incorporated to this Safety Data Sheet and its Annex.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

The mixture contains substances for which occupational exposure limits are set.

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date 25th January 2018 Version 5.0
Revision date 03rd June 2026

European Union

Commission Directive 2000/39/EC

Substance name (component)	Type	Value
xylenes	OEL 8 hours	221 mg/m ³
	OEL 8 hours	50 ppm
	OEL 15 minutes	442 mg/m ³
	OEL 15 minutes	100 ppm

Notes

Skin.

DNEL

ethanol			
Workers / consumers	Route of exposure	Value	Effect
Workers	Inhalation	950 mg/m ³	Chronic effects systemic
Workers	Inhalation	1900 mg/m ³	Acute effects local
Workers	Dermal	343 mg/kg bw/day	Chronic effects systemic
Consumers	Inhalation	114 mg/m ³	Chronic effects systemic
Consumers	Inhalation	950 mg/m ³	Acute effects local
Consumers	Dermal	206 mg/kg bw/day	Chronic effects systemic
Consumers	Oral	87 mg/kg bw/day	Chronic effects systemic

trizinc bis(orthophosphate)			
Workers / consumers	Route of exposure	Value	Effect
Workers	Inhalation	5 mg/kg	Chronic effects systemic
Workers	Dermal	83 mg/kg	Chronic effects systemic
Consumers	Inhalation	2.5 mg/kg	Chronic effects systemic
Consumers	Dermal	83 mg/kg	Chronic effects systemic
Consumers	Oral	0.83 mg/kg	Chronic effects systemic

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date 25th January 2018 Version 5.0
Revision date 03rd June 2026

xylene (mixture of isomers and ethylbenzene)

Workers / consumers	Route of exposure	Value	Effect
Workers	Inhalation	221 mg/m ³	Chronic effects systemic
Workers	Inhalation	442 mg/m ³	Acute effects systemic
Workers	Inhalation	442 mg/m ³	Acute effects local
Workers	Dermal	212 mg/kg bw/day	Chronic effects systemic
Consumers	Inhalation	65.3 mg/m ³	Chronic effects systemic
Consumers	Inhalation	260 mg/m ³	Acute effects systemic
Consumers	Inhalation	260 mg/m ³	Acute effects local
Consumers	Dermal	125 mg/kg bw/day	Chronic effects systemic
Consumers	Oral	12.5 mg/kg bw/day	Chronic effects systemic
Workers	Inhalation	221 mg/m ³	Chronic effects local
Consumers	Inhalation	65.3 mg/m ³	Chronic effects local

PNEC

ethanol

Route of exposure	Value
Freshwater environment	0.96 mg/l
Marine water	0.79 mg/l
Water (intermittent release)	2.75 mg/l
Microorganisms in sewage treatment	580 mg/l
Freshwater sediment	3.6 mg/kg of dry substance of sediment
Sea sediments	2.9 mg/kg of dry substance of sediment
Soil (agricultural)	0.63 mg/kg of dry substance of soil

trizinc bis(orthophosphate)

Route of exposure	Value
Freshwater environment	0.0206 mg/l
Marine water	0.0061 mg/l
Microorganisms in sewage treatment	0.1 mg/l
Freshwater sediment	117.8 mg/kg of dry substance of sediment
Sea sediments	56.5 mg/kg of dry substance of sediment
Soil (agricultural)	35.6 mg/kg of dry substance of soil

xylene (mixture of isomers and ethylbenzene)

Route of exposure	Value
Drinking water	0.327 mg/l
Marine water	0.327 mg/l
Water (intermittent release)	0.327 mg/l
Microorganisms in sewage treatment	6.58 mg/l

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date 25th January 2018 Version 5.0
Revision date 03rd June 2026

xylene (mixture of isomers and ethylbenzene)	
Route of exposure	Value
Freshwater sediment	12.46 mg/kg of dry substance of sediment
Sea sediments	12.46 mg/kg of dry substance of sediment
Soil (agricultural)	2.31 mg/kg of dry substance of soil

8.2. Exposure controls

Conditions of safe use of the registered product composition components specified in exposure scenarios to Safety Data Sheets of the components are given in Annex of the SDS, including the required additional measures restricting the exposure – see the exposure scenarios for the intended uses of the product.

General safety and hygienic measures. When working, do not eat, drink, smoke. Before the break and after the work, hands should be washed with soap and hot water, treated with barrier cream. Overall and local ventilation, effective extraction.

Eye/face protection



Protective goggles (closed eye protection) resistant to organic solvent or face shield.

Skin protection



Skin protection: Protective clothes with antistatic finish, protective shoes; treat unprotected skin with barrier cream.

Hand protection: Chemical resistant protective gloves (EN 374-1:2003). Suitable material – nitrile rubber (0,5 mm), butyl rubber (0,5 mm), fluoroelastomere (0,5 mm) and others, time of penetration corresponding to > 480 minutes. The time of penetration specified by the manufacturer should be followed and the glove replaced after expiration. If damaged, the gloves should be replaced immediately.

The selection of suitable protective gloves does not only depend on their material, but also on other qualitative features. Furthermore, since the mixture can be used for various purposes, mixed with other substances, the suitability of gloves for all purposes cannot be predetermined and must be verified in particular.

Respiratory protection



Don't breathe vapours. For short-time exposure or low concentration, use respirator with organic vapour and dust filter (protection level A/P2); for high concentration and long-term exposure, self-contained respirator is necessary.

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

Thermal hazard

Not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage. Ensure that containers are properly closed during storage, handling and transport. Secure storage areas against possible leakage of product into the environment (sewerage, water, soil - see 6.2). Do not flush product into drains or watercourses.

More information

In the Czech Republic: The monitoring procedure for the content of substances in workplace air and the specification of protective equipment is determined by the worker responsible for occupational safety and health protection of workers. Legal and natural persons doing business have the obligation to measure and control the values of concentrations of substances in the atmosphere of workplaces and to classify workplaces according to the categorization of work.

Exposure scenario is attached to the Safety Data Sheet.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	data not available
Odour	typical aromatic
Melting point/freezing point	data not available
Boiling point or initial boiling point and boiling range	data not available
xylene (mixture of isomers and ethylbenzene)	137-143 °C
Flammability	Flammable liquid and vapour.
Lower and upper explosion limit	data not available
xylene (mixture of isomers and ethylbenzene)	1 % 8 %
Flash point	>25 °C (EN ISO 2719)
xylene (mixture of isomers and ethylbenzene)	24-32 °C
Auto-ignition temperature	data not available
Decomposition temperature	data not available
pH	data not available
Kinematic viscosity	>20.5 mm ² /s at 40 °C
Solubility in water	insoluble
Solubility in fats	data not available
Partition coefficient n-octanol/water (log value)	data not available
Vapour pressure	data not available
Density and/or relative density	
Density	1.33 g/cm ³ at 20 °C (hardened mixture)
Relative vapour density	data not available
Particle characteristics	data not available
Form	Medium viscous liquid without mechanical impurities

9.2. Other information

Evaporation rate	data not available
Oxidising properties	The product has no oxidizing properties.

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

Ignition temperature	>400 °C (EN 14 522)
Explosive properties	The product does not have explosive properties.
Content of organic solvents (VOC)	0.37 kg/kg (hardened mixture)
Total organic carbon (TOC)	0.31 kg/kg (hardened mixture)
Solid content (dry matter)	47 % volume (hardened mixture)
VOC limit value	cat. A (j) SB: 500 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

When used in the standard way, there is not any dangerous reaction with other substances.

10.2. Chemical stability

The product is volatile and evaporates under standard temperature and pressure. It is stable when stored and handled under standard ambient conditions.

10.3. Possibility of hazardous reactions

The product is stable under normal conditions.

10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Hazardous substances in concentrations exceeding exposure limits may cause acute inhalation poisoning, depending on the concentration and duration of exposure. No toxicological data is available for the mixture.

Acute toxicity

Data for the mixture are not available. Based on the available data, the criteria for classification of the mixture are not met.

ethanol					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	2000 mg/kg		Rat (Rattus norvegicus)	

trizinc bis(orthophosphate)					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	5000 mg/kg		Rat (Rattus norvegicus)	

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date 25th January 2018 Version 5.0
Revision date 03rd June 2026

xylene (mixture of isomers and ethylbenzene)					
Route of exposure	Parameter	Value	Exposure time	Species	Sex
Dermal	LD ₅₀	>5000 mg/kg bw		Rabbit	
Inhalation (vapor)	LC ₅₀	6350-6700 ppm	4 hours	Rat (Rattus norvegicus)	M
Oral	LD ₅₀	>4000 mg/kg bw		Rat (Rattus norvegicus)	F
Oral	LD ₅₀	3523 mg/kg bw		Rat (Rattus norvegicus)	M

Skin corrosion/irritation

Causes skin irritation. Data for the components of the mixture are not available.

Serious eye damage/irritation

Causes serious eye damage. Data for the components of the mixture are not available.

Respiratory or skin sensitisation

May cause an allergic skin reaction. Data for the components of the mixture are not available.

Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

Toxicity for specific target organ - single exposure

May cause respiratory irritation. Data for the components of the mixture are not available.

Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure. Data for the components of the mixture are not available.

Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date 25th January 2018 Version 5.0
Revision date 03rd June 2026

11.2. Information on other hazards

Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

Other information

not available

SECTION 12: Ecological information

12.1. Toxicity

The complete mixture has not been tested. The classification is based on the calculation method. Information on toxic effects are based on the effects of the substances, the data are taken from the safety data sheets of raw materials. The mixture is classified as dangerous for the environment. Toxic to aquatic life with long lasting effects. The mixture is a source of volatile organic emissions. Avoid release to the environment.

Acute toxicity

ethanol				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	8140 mg/l	96 hours	Fish (Oncorhynchus mykiss)	
EC ₅₀	9248 mg/l	48 hours	Daphnia (Daphnia magna)	
EC ₅₀	5000 mg/l	72 hours	Algae (Selenastrum capricornutum)	

trizinc bis(orthophosphate)				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	0.3-5.59 mg/l	96 hours	Fish (Oncorhynchus mykiss)	
LC ₅₀	0.89-0.96 mg/l	48 hours	Crustaceans	
EC ₅₀	0.29-0.32 mg/l	72 hours	Algae and other aquatic plants	

xylene (mixture of isomers and ethylbenzene)				
Parameter	Value	Exposure time	Species	Environment
LC ₅₀	2.6 mg/l	96 hours	Fish (Oncorhynchus mykiss)	
EC ₅₀	1 mg/l	48 hours	Daphnia (Daphnia magna)	
LC ₅₀	2.2 mg/l	72 hours	Algae (Pseudokirchneriella subcapitata)	

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date 25th January 2018 Version 5.0
Revision date 03rd June 2026

Chronic toxicity

xylene (mixture of isomers and ethylbenzene)				
Parameter	Value	Exposure time	Species	Environment
NOEC	>1.3 mg/l	56 days	Fish (Oncorhynchus mykiss)	
NOEC	0.96-1.17 mg/l	7 days	Invertebrates (Ceriodaphnia dubia)	

12.2. Persistence and degradability

Data for the mixture are not available.

Biodegradability

xylene (mixture of isomers and ethylbenzene)					
Parameter	Method	Value	Exposure time	Environment	Result
	OECD 301F	>90 %	28 days		Easily biodegradable

12.3. Bioaccumulative potential

Data for the mixture are not available.

xylene (mixture of isomers and ethylbenzene)	
Parameter	Value
BCF	25900 ml/kg
Log Pow	3.12-3.2

12.4. Mobility in soil

The mixture is a liquid insoluble in water, in case of leakage into environment, it may be dispersed over large distances and penetrate into underground water. It contains components with the potential of mobility in soil. When released into the soil may occur due to contamination of groundwater.

xylene (mixture of isomers and ethylbenzene)	
Parameter	Value
Koc	48-129

12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

12.7. Other adverse effects

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

Volatile organic substances contained in the mixture have the potential to damage ozone layer. Possible impacts on the waste water treatment plant: the concentration of this substance in the waste water to be treated must be in a controlled mode in accordance with the sewage regulations. The mixture may contaminate soil and water and may damage the fauna and flora. According to the Water Management Act, Act No. 254/2001 Coll., The product is considered a dangerous substance and a dangerous substance according to Annex No. 1 of the Water Management Act. Prevent substance from entering groundwater, soil and sewage system.

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

Waste type code

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

Packaging waste type code

15 01 10* packaging containing residues of or contaminated by hazardous substances

(*) - Hazardous waste according to Directive 2008/98/EC on hazardous waste

SECTION 14: Transport information**14.1. UN number or ID number**

UN 1263

14.2. UN proper shipping name

PAINT

14.3. Transport hazard class(es)

3 Flammable liquids

14.4. Packing group

III

14.5. Environmental hazards

The product is dangerous for the environment.

14.6. Special precautions for user

Reference in the Sections 4 to 8. The product is transported in ordinary and covered means of transport, protected against the weather, shocks and falls.

14.7. Maritime transport in bulk according to IMO instruments

Not classified.

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

Additional information

Hazard identification No.

UN number

Classification code

Safety signs

30
1263

F1

3+ hazardous for the environment



Tunnel restriction code

(D/E)

Air transport - ICAO/IATA

Packaging instructions passenger 355

Cargo packaging instructions 366

Marine transport - IMDG

EmS (emergency plan) F-E, S-E

MFAG 310

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

15.2. Chemical safety assessment

Chemical safety assessment was carried out on the individual substances of the mixture. The respective exposure scenarios are incorporated in Annex of this Safety Data Sheet.

SECTION 16: Other information

A list of standard risk phrases used in the safety data sheet

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a doctor.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	Agreement concerning the international carriage of dangerous goods by road
Aquatic Acute	Hazardous to the aquatic environment
Aquatic Chronic	Hazardous to the aquatic environment (chronic)
Asp. Tox.	Aspiration hazard
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EC ₅₀	Concentration of a substance when it is affected 50 % of the population
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency Response Procedures for Ships Carrying Dangerous Goods
EU	European Union
EuPCS	European Product Categorisation System
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Flam. Liq.	Flammable liquid
IATA	International Air Transport Association
IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

IUPAC	International Union of Pure and Applied Chemistry
LC ₅₀	Lethal concentration of a substance in which it can be expected death of 50% of the population
LD ₅₀	Lethal dose of a substance in which it can be expected death of 50% of the population
log K _{ow}	Octanol-water partition coefficient
NOEC	No observed effect concentration
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulation concerning the International Carriage of Dangerous Goods by Rail
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitization
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
UN number	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

The product is exclusively intended for use in installations authorised according to Directive 1999/13/EC where emission limiting measures provide alternative means of achieving at least equivalent VOC emission reductions.

Information about data sources used to compile the Safety Data Sheet

Commission Regulation (EU) 2020/878 of 18 June 2020. REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 5.0 replaces the SDS version from Monday, 25 September 2023. Changes were made in sections 2, 11, 12, 13 and 16.

More information

Classification procedure - calculation method.

Statement

according to Commission Regulation (EU) 2020/878 as amended

TELPOX P100 S

Creation date	25th January 2018	Version	5.0
Revision date	03rd June 2026		

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.

Annex to the Product Safety Data Sheet - EXPOSURE SCENARIO RECOMMENDATION ON SAFE USE OF THE MIXTURE

1. Industrial use

Application sector	: SU 3
Chemical product category	: PC9a
Partial processes covered by exposure scenario:	PROC1, PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC10, PROC13, PROC15
Environmental release	: ERC4

Basic conditions to control the hazard for workers:

Duration of work activities	: Covers exposure up to 8 h/d (unless otherwise specified)
Concentration	: Work with standard coating composition or coating composition thinned by solvents containing the same volatile components as the coating composition is anticipated.
Temperature	: Work at temperature up to 20 °C higher than site temperature is anticipated except for the coating composition's drying and hardening processes at increased temperature.
General risk management measures	: Wear protective working clothes. Wear protective gloves and eye protection if in danger of contact with the coating composition (see section 8.2. of the SDS). Basic training required. : Use respiratory protection if NPK or PEL values are exceeded (see section 8 of the SDS). : Abide by general principles of safe and hygienic work with chemical substances. : Workplaces must meet the requirements for work with flammable liquids capable of producing explosive mixtures of vapours with air. : The workplace must meet the requirements against accidental leaks of the product into water or soil.
Site where the activities are performed	: Indoor use is anticipated.

Additional requirements to control the hazard for workers carrying out partial work activities:

Partial work activities with the product (Partial contributing scenarios)	Process category	Required additional measures to control worker exposure
Pumping from/to containers and devices within a closed system with no possibility to release emission	PROC 1 Use within closed production process	Does not require further risk control measures.
Pumping the coating composition from/to containers and devices at non dedicated facility with potential human and environment exposure	PROC 8a Transfer of the product (charging / discharging) to/from vessels/large containers at non dedicated facilities	Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).
Pumping the coating composition from/to containers and devices at non dedicated facility with potential human and environment exposure	PROC 8b Transfer of the product (charging / discharging) to/from vessels/large containers at dedicated facilities	Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).
Mixing, blending, thinning of coating composition in open devices with possible exposure to volatile components of the coating composition	PROC5 Mixing or blending in batch processes at mixture manufacturing (excl. charging and discharging of vessels).	Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).
Application by spraying.	PROC 7 Industrial spraying.	Robotic spraying in closed chambers or closed cabs with laminar extraction. In course of spraying, enter the chambers only with self-contained respirator. Manual spraying in spraying chambers with laminar flow of extracted air directed from the worker or in intensively ventilated spaces (5-10 air exchanges per hour) with respiratory protection (half-face or full-face respirator) provided with type A/P2 filter.
Manual coating composition application by roller, brush or palette knife.	PROC 10 Roller, palette knife or brush application	Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).
Dipping or pouring application of coating composition.	PROC 13 Treatment of articles by dipping and pouring	Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).
Free drying of coating composition film at standard or slightly increased ambient temperature (by max. 20 °C)	PROC 4 Use within batch or other process where opportunity for exposure arises	Carry out in well ventilated spaces (3-5 air exchanges per hour).
Continuous drying and hardening processes of the coating composition film at increased temperature in drying tunnels equipped with vapour extraction	PROC 2 Use within continuous chemical production process with occasional controlled exposure (e.g. at sampling).	Does not require further risk control measures.
Batch drying and hardening processes of the coating composition film at increased temperature in extracted chambers	PROC 3 Use within closed batch process of mixture manufacturing.	Does not require further risk control measures.

Machine cleaning and washing of closed tanks, containers and devices equipped with vapour extraction	PROC 3 Use within closed batch process of mixture manufacturing	Does not require further risk control measures.
Manual cleaning of small containers, application devices and tools	PROC 10 Roller or brush application (by a tool held in hand) PROC8a Transfer of the product (charging / discharging) to/from vessels/large containers at non dedicated facilities	Local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour).
Laboratory checks on the coating composition	PROC 15 Use as laboratory reagent (laboratory work with the product)	Handling in a fume hood or in the presence of vacuum ventilation.
Activities involving product waste and waste contaminated by the product		If in risk of contact with waste, wear protective gloves. Store the waste in closable containers stored in well ventilated storages or outdoor.

Additional requirements to control environmental hazards

Air emission control	When spraying, remove fly coating mist from the air extracted from the work site. If the limits for solvent consumption defined in Ordinance no. 415/2012 Coll. are exceeded, use solvent recuperation from waste air or remove the solvents by incineration or other processes guaranteeing observation of emission parameters specified in air protection regulations.
Water emission control	Store the coating and waste contaminated by coat in buildings structurally protected from leakage release and emergency release to surface and ground water. Treat water contaminated by coat compounds and remove solid impurities and organic compounds by sedimentation, filtration, biological treatment processes or special processes developed for treatment of water contaminated by coating compositions before discharging to surface water. When discharging the treated waste water, observe the contamination parameters specified for the involved facility by water management authority.
Disposal of waste	Dispose of coat waste and materials contaminated by coat and its compounds in cooperation with authorised persons as of hazardous waste. Dispose of solvent waste from tools and device cleaning as of hazardous waste. Prevent release or discharge of any liquid waste to surface and ground water unless it is treated and coating composition compounds are removed.

2. Professional use

Application sector	: SU 22
Chemical product category	: PC9a
Partial processes covered by exposure scenario:	PROC3, PROC4, PROC5, PROC8a, PROC8b, PROC10, PROC11, PROC13, PROC15, PROC19
Environmental release	: ERC 8a, ERC 8d

Basic conditions to control the hazard for workers:

Duration of work activities	: Covers exposure up to 8 h/d (unless otherwise specified)
Concentration	: Work with standard coating composition or coating composition thinned by solvents containing the same volatile components as the coating composition is anticipated.
Temperature	: Work at temperature up to 20 °C higher than site temperature is anticipated except for the coating composition's drying and hardening processes at increased temperature.
General risk management measures	: Wear protective working clothes. Wear protective gloves and eye protection if in danger of contact with the coating composition (see section 8.2. of the SDS). Basic training required. : Use respiratory protection if NPK or PEL values are exceeded (see section 8 of the SDS). : Abide by general principles of safe and hygienic work with chemical substances. : Workplaces must meet the requirements for work with flammable liquids capable of producing explosive mixtures of vapours with air. : The workplace must meet the requirements against accidental leaks of the product into water or soil.
Site where the activities are performed	: Indoor and outdoor use is anticipated.

Additional requirements to control the hazard for workers carrying out partial work activities:

Partial work activities with the product (Partial contributing scenarios)	Process category	Required additional measures to control worker exposure
Pumping the coating composition from/to containers and devices at non dedicated facility with potential human and environment exposure	PROC 8a Transfer of the product (charging / discharging) to/from vessels/large containers at non dedicated facilities	Indoor: local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour). Outdoor: secure catch dripping paint

Pumping the coating composition from/to containers and devices at non dedicated facility with potential human and environment exposure	PROC 8b Transfer of the product (charging / discharging) to/from vessels/large containers at dedicated facilities	Indoor: local air extraction at potential emission release or good ventilation (5-10 air exchanges per hour). Outdoor: does not require further risk control measures
Mixing, blending, thinning of coating composition in open devices with possible exposure to volatile components of the coating composition	PROC5 Mixing or blending in batch processes at mixture manufacturing (excl. charging and discharging of vessels).	Indoor: local air extraction at potential emission release or good ventilation (3-5 air exchanges per hour). Outdoor: working process a maximum of 4h per day does not require further risk control measures or use respiratory protection with filter type A.
Application by spraying.	PROC 11 Non industrial spraying.	Indoor: do spraying in spraying chambers with laminar flow of extracted air directed from the worker or in intensively ventilated spaces (5-10 air exchanges per hour) with respiratory protection (half-face or full-face respirator) provided with type A/P2 filter. Outdoor: use respiratory protection with filter type A/P2.
Manual coating composition application by roller, brush or palette knife.	PROC 10 Roller, palette knife or brush application	Indoor: local air extraction at potential emission release or good ventilation (5-10 air exchanges per hour). Outdoor: does not require further risk control measures
Dipping or pouring application of coating composition.	PROC 13 Treatment of articles by dipping and pouring	Indoor: local air extraction at potential emission release or good ventilation (5-10 air exchanges per hour). Outdoor: use respiratory protection with filter type A.
Free drying of coating composition film at standard or slightly increased ambient temperature (by max. 20 °C)	PROC 4 Use within batch or other process where opportunity for exposure arises	Indoor: carry out in well ventilated spaces (5--10 air exchanges per hour). Outdoor: does not require further risk control measures
Batch drying and hardening processes of the coating composition film at increased temperature in extracted chambers	PROC 3 Use within closed batch process of mixture manufacturing.	Does not require further risk control measures.
Manual cleaning of small containers, application devices and tools	PROC 10 Roller or brush application (by a tool held in hand)	Indoor: local air extraction at potential emission release or good ventilation (5-10 air exchanges per hour). Outdoor: does not require further risk control measures
Laboratory checks on the coating composition	PROC 15 Use as laboratory reagent (laboratory work with the product)	Handling in a fume hood or in the presence of vacuum ventilation.
Manual activities involving hand contact	PROC19 Hand-mixing with intimate contact and only PPE available	Indoor. Use protective gloves, local air extraction at potential emission release or good ventilation Outdoor: use protective gloves
Activities involving product waste and waste contaminated by the product		If in risk of contact with waste, wear protective gloves. Store the waste in closable containers stored in well ventilated storages or outdoor.

Additional requirements to control environmental hazards

Air emission control	Does not require special risk control measures
Water emission control	Store the paints and waste contaminated by paints in buildings structurally protected from leakage release and emergency release to surface and ground water. Clean up waste water contaminated by paints in the Municipal wastewater treatment plants before discharging to surface water or capture or dispose them as hazardous waste in cooperation with the authorized person. Overspray and drips paint as possible to capture and dispose as hazardous waste.
Disposal of waste	Prevent leakage or discharge of any liquid waste into surface and groundwater unless it is cleaned up from the paint compounds. Dispose of paint waste and materials contaminated by paints and its compounds in cooperation with authorised persons as of hazardous waste. Dispose of solvent waste from tools and device cleaning as of hazardous waste.